

MakeID

M100C

INDUSTRIAL LABEL PRINTER

LABEL PRI



CHONGQING PINSHENG TECHNOLOGY CO., LTD.

M100C

Industrial Label Printer

KEY FEATURES

-  1-inch high-precision 300 dpi print head, delivering sharper, clearer and more refined printing
-  Rubber-coated housing design with 1.5 m drop resistance; sealed dust-proof cover ensures clean and stable printing
-  Support PC editing software (Windows/macOS) and mobile apps (Android/iOS) for seamless cross-platform collaboration
-  2600 mAh lithium battery, providing long-lasting power and worry-free operation for outdoor and on-site use
-  All-in-one consumable design for quick and easy installation; automatically matches label templates to improve operational efficiency



TECHNICAL SPECIFICATIONS

ITEM	SPECIFICATION
Printing Method	thermal transfer
Resolution	300dpi
Print Width	1 inch (25.4 mm)
Print Speed	25.4mm/s
Dimensions	146*118*62mm
Weight	600g
Battery	2600mAh
Continuous Printing Time	2.5 hours (25 °C, 12.5% print density)
Charging Port	Type-C
Interface	USB(type-C),Bluetooth
Operation Method	Mobile APP(MakeID Label Pro)、PC(MakeID Label Design)
Cutter	Manual Cutter
Consumables	All-in-one consumables
Accessories	Magnet, belt clip(optional)
Operating Environment	0-40°C, 20%-90% RH (non-condensing)
Storage Environment	-20°C-+60°C, 5%-93% RH(non-condensing)

F-Series Cable Labels

Material:Matte PP film

Features:Tear-resistant, high-temperature resistant, and resistant to common chemical solvents

Applications:Pigtail, Ethernet Cable, Power Cable, Feeder Cable and other cables



Model	Size(axb+c)	Specifications	Color	
WQS-02F(107)/G	25mm*38mm+40mm	100 pcs/case	White/Red/Yellow/Blue/Green 	
WQS-07F(107)/G	25mm*38mm+25mm	123 pcs/case	White/Red/Yellow/Blue/Green 	

Flat Surface Labels

Material:Matte PP film

Features:Tear-resistant,high-temperature resistant, and resistant to common chemical solvents

Applications:Fiber Optic Terminals,switch,server,workstation,cabinet



Model	Size (a×b)	Specifications	Color	
WP20-40(107)/G	20mm*40mm	188 pcs/case	White 	
WP25-25(107)/G	25mm*25mm	291 pcs/case	White 	
WP25-50(107)/G	25mm*50mm	152 pcs/case	White 	
WP25-75(107)/G	25mm*75mm	104 pcs/case	White,Red 	

Continuous Labels

Material:Matte PP film

Features:Tear-resistant,high-temperature resistant, and resistant to common chemical solvents

Applications:control panels,distribution box or other equipment with regular ports/ switches/indicator lights



Model	Size (a×b)	Specifications	Color	
WD19-6(107)/G	19mm*6.5m	6,5 m/case	White,Yellow 	
WD25-6(107)/G	25.5mm*6.5m	6,5 m/case	White 	

Telecom Flexible Nylon Label

Material :Nylon

Features: Flexibility,good adhesion to curved or irregular surfaces, with resistance to chemical corrosion,high temperatures, low temperatures and common solvents

Application:cable, cable end, patch cord, and in-rack cabling identification



Model	Size (a×b)	Specifications	Color	
WD10-5(399)/G	10mm*5m	5m/case	White	
WD13-5(399)/G	13mm*5m	5m/case	White	
WD19-5(399)/G	19mm*5m	5m/case	White	
WD25-5(399)/G	25.5mm*5m	5m/case	White	

Wrap-around Labels

Material:Matte polyethylene film

Features:Excellent flexibility and conformability, with strong resistance to water and moisture, and outstanding chemical resistance

Application:Wires, cables, and compression-resistant hoses



Model	Size (a×b)	Specifications	Color	
WD19-4(302)/G	19mm*4.5m	4.5 m/case	White	
WD25-4(302)/G	25.5mm*4.5m	4.5 m/case	White	
WP25-25(302)/G	25mm*25mm	250pcs/case	White	

Heat-Shrink Tubing Labels

Material:Halogen-free,eco-friendly polyolefin heat-shrink tubing

Features:Good Print Durability, Solvent Resistance, Excellent Low-Temperature Flexibility, Superior Aging Resistance, and Flame Retardancy

Application:Wires,cables,strands



Model	Size (a×b)	Specifications	Color	
LRS-32/G	6.1mm x 2.1m, φ3.2mm	2.1 m/case	White,Yellow	
LRS-48/G	8.4mm x 2.1m, φ4.8mm	2.1 m/case	White,Yellow	
LRS-64/G	11.2mm x 2.1m, φ6.4mm	2.1 m/case	White,Yellow	
LRS-95/G	6.8mm x 2.1m, φ9.5mm	2.1 m/case	White,Yellow	

Telecom All-Weather Labels

Material: PET

Features: Tear Resistance, High-Temperature Resistance, and Resistance to Common Chemical Solvents

Application: Communication racks, equipment enclosures, patch panels, distribution cabinets



Model	Size (a×b)	Specifications	Color	
WD10-6(456)/G	10mm*6.5m	6,5 m/case	White	A diagram of a white rectangular label with a wavy bottom edge. The width is labeled 'a' and the length is labeled 'b'.
WD13-6(456)/G	13mm*6.5m	6,5 m/case	White	
WD19-6(456)/G	19mm*6.5m	6,5 m/case	White	
WD25-6(456)/G	25.5mm*6.5m	6,5 m/case	White	



LABEL ALL THINGS · PERCEIVE THE WORLD



Chongqing Pinsheng Technology Co., Ltd.

FT@makeid.com www.makeid.com V1.0
Add: No. 7-1, Building 5, Middle Section of Huangshan Avenue,
Northern New District, Chongqing, China